

## BUS AIR CONDITIONING

## **ADVANCED FEATURES**

- Designed To Fit The Front Wall Of The Thomas C2
- Attractive ABS Dark Gray Cover Matches The TBB C2
- Pressure Switches Located At The Evaporator
   For Maxium Compressor Protection
- O-Ring Connections For Maximum Leak Protection
- Utilized Drain Pan Construction Eliminates
   Condensation Problems
- Two High Capacity Dual Blowers
- Enhanced Copper Tube Aluminum Fin Coils
- Direct Conditioned Air Discharge
- Drop-In One-Piece Construction Simplifies
   Installation Time and Provides Maximum
   Head Clearance and Clean OEM Appearance
- Easy Access Return Air Filter Helps To Reduce Service Time



## **SPECIFICATIONS**

**RATING:** Up to 60,000 Btu/Hr. IMACA **AIRFLOW:** 1,600 CFM (2712 M3/hr.)

AMPERAGE DRAW: 19 Amps @ 13.5 Volts 10 Amps @ 27 Volts


WEIGHT: 43 lbs.


**EVAPORATOR BLOWERS: Two** 

Specifications subject to change without notice.

## **OPTIONS**

- Adjustable or Fixed Air Outlet Louvers
- 12 Volt or 24 Volt Motors
- Durable ABS Cover or Flush Mount Lightweight Metal Face Plate
- Gray or White Cover







CLIMATE COMFORT IN MOTION

715 Willow Springs Lane York, PA 17406 717 / 767-2775 Toll Free: 877 / 228-4247

Fax: 717 / 767-3658



WWW.PROAIRLLC.COM

WWW.ACTUSA.US.COM