



ISOMETRIC VIEW

- NOTES:
- 1) USE SERVICABLE THREADLOCKER ON ALL FASTENERS TO ENGINE COMPONENTS AND TORQUE **ALL** BOLTS TO S.A.E. SPECIFICATIONS.
 - 2) SEE "TRANSARCTIC A/C COMPRESSOR MOUNT INSTALLATION DISCLAIMER".
 - 3) WEIGHT: 16.25 LBS.

ITEM	QTY	U/M	PART NUMBER	DESCRIPTION
9	4	EACH	WL007000	WASHER, LOCK, 7/16", 8, PLT
8	2	EACH	WL006000	WASHER, LOCK, 3/8", 8, PLT
7	4	EACH	WFP07000	WASHER, FLAT, 7/16", 2, PLT
6	2	EACH	WFM06000	WASHER, FLAT, 3/8", 2, PLT
5	1	EACH	SCD29213	SPACER, COL, DRL, 29.21mm x 25.4o x 12.7i
4	4	EACH	NTP07000	NUT, HEX, 7/16-14UNC, 5, PLT
3	2	EACH	BTQ06150	BOLT, HEX, 3/8-16UNC, 1.50", 8, PLT
2	1	EACH	BMN80010	BKT, MAIN, SLIDE, ASSY, IC, RE300
1	1	EACH	BMC90015	BKT, WELDMT, ALT EXTENSION, HDX, '16

BILL OF MATERIALS			
DRAWN	jrdriguez	5/31/2016	
CHECKED	Jose Rodriguez	5/31/2016	
APPROVED	James Stewart	5/31/2016	
DATE	Dale Mason	5/31/2016	
TITLE			KIT, PLATFORM, O5G W/ ALT, '16
SIZE			DWG NO KBT94195
SCALE			1:2
SHEET			1 OF 1

REV	ECN	DESCRIPTION	DATE	BY
A		RELEASED TO PROTOTYPE	5/31/2016	JRR

UNSPECIFIED TOLERANCES: ALL DIMS IN INCHES
 ONE DECIMAL PLACE (X1) .10
 TWO DECIMAL PLACE (X2) .05
 THREE DECIMAL PLACE (X3) .010
 FRACTIONAL: 1/16" .0625



DRAWING UNIT OF MEASURE: MM (INCH)